

WHAT IS CLAIMED IS:

1. A mobility management node comprising:

mobility management means for correlating a home address in a home network of a mobile node with a c/o address in a network where the mobile node is located after movement;

binding storing means for storing the home address and the c/o address of the mobile node correlated with each other by the mobility management means;

transition detecting means for monitoring transition of the c/o address stored in the binding storing means, and for detecting a prefix of the c/o address before the transition and a prefix of the c/o address after the transition;

transition history storing means for storing a transition frequency of the c/o address in correlation with the prefix of the c/o address before the transition and the prefix of the c/o address after the transition detected by the transition detecting means;

paging area forming means for extracting predetermined combinations of the prefix of the c/o address before the transition with the prefix of the c/o address after the transition, stored by the transition history storing means, and for generating paging area information by a set of said prefixes

included in the extracted combinations; and

paging area notifying means for notifying the mobile node of the paging area information generated by the paging area forming means.

5 2. The mobility management node according to Claim 1, wherein the paging area forming means extracts combinations of the prefix before the transition with the prefix after the transition with each of which a transition frequency over a predetermined reference
10 value is correlated among the transition frequencies stored by the transition history storing means, extracts combinations having the common prefixes, out of the extracted combinations, and generates the paging area information by a set of the prefixes included in
15 the combinations finally extracted.

3. The mobility management node according to Claim 2, further comprising:

registration time interval measuring means for measuring a registration time interval during which an
20 address of the mobile node is continuously registered in the binding storing means; and

update frequency measuring means for measuring an update frequency of the c/o address of the mobile node stored in the binding storing means;

25 wherein the paging area forming means uses a plurality of predetermined reference values different

from each other to generate the paging area information as to each of the plurality of predetermined reference values, thereby generating a plurality of paging area information items, and

5 wherein the paging area notifying means derives an update frequency per unit time of the c/o address of the mobile node, based on the registration time interval of the mobile node measured by the registration time interval measuring means and the
10 update frequency of the mobile node measured by the update frequency measuring means, and notifies the mobile node of a paging area information item selected out of the plurality of paging area information items in accordance with the update frequency per unit time
15 of the c/o address of the mobile node, based on a predetermined rule defined so that a number of prefixes included in the paging area information increases against increase of the update frequency per unit time of the c/o address.

20 4. A paging area forming method comprising:

 a mobility management step wherein mobility management means correlates a home address in a home network of a mobile node with a c/o address in a network where the mobile node is located after
25 movement, and stores the addresses in correlation with each other into binding storing means;

a transition detecting step wherein transition detecting means monitors transition of the c/o address stored in the binding storing means, detects a prefix of the c/o address before the transition and a prefix of the c/o address after the transition, and lets transition history storing means store a transition frequency of the c/o address in correlation with the prefix of the c/o address before the transition and the prefix of the c/o address after the transition;

a paging area forming step wherein paging area forming means extracts predetermined combinations of the prefix of the c/o address before the transition with the prefix of the c/o address after the transition, stored in the transition history storing means, and generates paging area information by a set of the prefixes included in the extracted combinations; and

a paging area notifying step wherein paging area notifying means notifies the mobile node of the paging area information generated by the paging area forming means.

5. The paging area forming method according to Claim 4, wherein in the paging area forming step the paging area forming means extracts combinations of the prefix before the transition with the prefix after the transition with each of which a transition frequency

over a predetermined reference value is correlated among the transition frequencies stored by the transition history storing means, extracts combinations having the common prefixes, out of the extracted combinations, and generates the paging area information by a set of the prefixes included in the combinations finally extracted.

6. The paging area forming method according to Claim 5, further comprising a registration time interval measuring step wherein registration time interval measuring means measures a registration time interval during which an address of the mobile node is continuously registered in the binding storing means; and

an update frequency measuring step wherein update frequency measuring means measures an update frequency of the c/o address of the mobile node stored in the binding storing means;

wherein in the paging area forming step the paging area forming means uses a plurality of predetermined reference values different from each other to generate the paging area information as to each of the plurality of predetermined reference values, thereby generating a plurality of paging areas, and

wherein in the paging area notifying step the

5 paging area notifying means derives an update frequency
per unit time of the c/o address of the mobile node,
based on the registration time interval of the mobile
node measured by the registration time interval
measuring means and the update frequency of the mobile
node measured by the update frequency measuring means,
and notifies the mobile node of a paging area
information item selected out of the plurality of
10 paging area information items in accordance with the
update frequency per unit time of the c/o address of
the mobile node, based on a predetermined rule defined
so that a number of prefixes included in the paging
area information increases against increase of the
update frequency per unit time of the c/o address.

15 7. A mobility management program for letting a
computer function as:

mobility management means for correlating a home
address in a home network of a mobile node with a c/o
address in a network where the mobile node is located
20 after movement;

binding storing means for storing the home
address and the c/o address of the mobile node
correlated with each other by the mobility management
means;

25 transition detecting means for monitoring
transition of the c/o address stored in the binding

storing means, and for detecting a prefix of the c/o address before the transition and a prefix of the c/o address after the transition;

5 transition history storing means for storing a transition frequency of the c/o address in correlation with the prefix of the c/o address before the transition and the prefix of the c/o address after the transition detected by the transition detecting means;

10 paging area forming means for extracting predetermined combinations of the prefix of the c/o address before the transition with the prefix of the c/o address after the transition, stored by the transition history storing means, and for generating paging area information by a set of said prefixes
15 included in the extracted combinations; and

paging area notifying means for notifying the mobile node of the paging area information generated by the paging area forming means.